

Spatial and Temporal Patterns in Sequential Precision Reach Movements

Justin M. Haney¹, Tianke Wang¹, Clive D'Souza¹, Monica L. H. Jones², Matthew P. Reed^{1,2}

¹Department of Industrial and Operations Engineering, University of Michigan, Ann Arbor, MI, USA;

²University of Michigan Transportation Research Institute, Ann Arbor, MI, USA

Introduction: Sequential reach tasks are a common component of manual assembly jobs. These tasks typically involve manipulating a work object or material and reaching to successive target locations with different precision requirements. Ergonomics research on the control of hand movements has largely focused on tasks requiring discrete reaches (e.g., Bootsma & Van Wieringen, 1992; Hoff & Arbib, 1993; Jeannerod, 1984; Marteniuk et al., 1990).

The objective of this paper was to investigate spatial and temporal effects of pulley design parameters (outer diameter and groove width) on the trajectory of the threading hand in sequential reaches with different precision requirements. Additionally, we propose a scheme to segment hand trajectories into control phases based on the fingertip trajectory speed profile. Segmenting sequential reach tasks into discrete movements between two consecutive target locations will be useful towards developing models of sequential reaching movements and performance for ergonomic analysis.

Methods: Twelve right-handed adults, ages 20-26 years, participated in a laboratory experiment that required threading polyester string through a system of pulleys mounted on an acrylic work surface. Interchangeable pulleys were arranged on the perimeter of a semicircle with a radius of 46 cm at azimuths of 0°, 45°, 90°, 135°, and 180° relative to a constant origin pulley located at the center. The height of the pulleys above the floor was adjusted to place the center pulley at the participant's standing elbow height. The thread was pulled from a spool located below the center pulley. The task involved threading the pulleys in the following sequence: origin-180°-origin-135°-origin-90°-origin-45°-origin-0°-origin. We conducted a full-factorial experiment with three pulley outer diameters (OD: 38-mm, 76-mm, and 152-mm), three groove widths (GW: 3-mm, 6-mm, and 9-mm), five pulley locations (0°, 45°, 90°, 135°, and 180°), and two threading directions (clockwise and counterclockwise), with 3 repetitions per condition. Participants were instructed to complete the task as quickly as possible while also ensuring each pulley was threaded successfully.

A motion capture marker triad on the hand dorsum tracked hand motions during the task. Hand trajectories were analyzed separately for each of the 5 origin-destination pulley location pairs. Speed profiles were analyzed to identify transition points between the transport phase, where the hand is reaching from the origin to the destination location, and the pulley interaction phase, where the hand is engaged in threading the destination pulley. The start and end points of the pulley interaction phase correspond to the first and last local speed minima that occur below a threshold set at 100-mm/s above the minimum speed when the trajectory is within the region of the destination pulley. The angle (α) and radius (R) of the hand position, relative to the destination pulley center, were estimated at the start (t_1) and end (t_2) points of the pulley interaction phase. Repeated measures ANOVA was used to test the effects of OD, GW, pulley location, and threading direction on the time spent in the pulley interaction phase ($T_{PI} = t_2 - t_1$), $R_1, R_2, \alpha_1, \alpha_2$, and the difference between α_1 and α_2 ($\alpha_{PI} = \alpha_2 - \alpha_1$).

Results:

Temporal parameters: Pulley OD ($p < 0.001$), GW ($p < 0.001$), location ($p = 0.002$), and the threading direction x pulley location interaction ($p < 0.001$) had a significant effect on T_{PI} . Larger GW corresponded to less T_{PI} (GW: Mean±SE, 3-mm: 772±34 ms, 6-mm: 473±23 ms, 9-mm: 351±18 ms). Pulley OD of 152-mm required significantly more T_{PI} (713±35 ms) compared to the 38-mm (449±21 ms) and 76-mm (433±21 ms) OD. The CW threading direction required significantly less T_{PI} for the 0°, 45° and, 90° pulley locations, while CCW threading direction took more T_{PI} for the 135° and 180° pulley locations.

Spatial Parameters: The effects of OD ($p < 0.001$) and pulley location ($p < 0.001$) were significant for R_1 . Larger OD corresponded to increased R_1 , i.e., 38-mm OD: 76 ± 1 -mm, 76-mm OD: 87 ± 1 -mm, and 152-mm OD: 119 ± 1 -mm. Additionally, R_1 increased significantly as the pulley location changed from 0° - 180° . Similar trends were observed for R_2 across OD and pulley location. The main effects of OD ($p < 0.001$), pulley location ($p < 0.001$), and threading direction ($p < 0.001$) and the interaction between pulley location and threading direction ($p < 0.001$) were significant for α_1 . Larger OD corresponded to a greater α_1 (38-mm OD: $24 \pm 1^\circ$, 76-mm OD: $34 \pm 1^\circ$, 152-mm OD: $53 \pm 1^\circ$). At the 180° pulley location, α_1 was significantly greater for the CCW vs. CW threading direction. At the 0° , 45° and, 90° pulley locations, α_1 was greater for the CW vs. CCW threading direction. Similar trends were observed for α_2 across task parameters. The main effect of pulley OD on α_{PI} was significant ($p < 0.001$) with a larger α_{PI} for the 152-mm OD ($22 \pm 1^\circ$) compared to the 38-mm OD ($15 \pm 1^\circ$) and 76-mm OD ($11 \pm 1^\circ$).

Discussion: These results show that pulley design parameters in a sequential reach task systematically influence the spatial properties and transition timing of hand motion trajectories between phases. Narrower GW increased the precision requirement and corresponded to slower times. Participants took more time threading the larger OD. Shorter threading times occurred when participants had a direct line of sight with the pulley groove. Pulley OD influenced the radius of the hand position at the start and end of the pulley interaction phase, whereas pulley GW had no effect. The increase in R_1 and R_2 for pulleys located on the contralateral side compared to the lateral side was attributed to need for line of sight with the pulley groove since the hand obstructs the view of the pulley edge on the contralateral side.

Conclusions: Analysis of sequential reaches needs to consider individual target locations and design parameters. Our findings also show the potential for modeling sequential reaches as a series of discrete reaches. A scheme to segment hand trajectories into control phases based on the fingertip trajectory speed profile was presented. Further investigation is necessary in sequential reach tasks with more realistic and complex work configurations observed in industrial settings.

Acknowledgments: This work was supported by the partners of the Human Motion Simulation Laboratory at the University of Michigan, who include Fiat Chrysler Automobiles, Ford Motor Company, General Motors, and Proctor and Gamble, as well as by traineeship support (to JH) received through the training grant T42-OH008455 from the National Institute for Occupational Safety and Health, Centers for Disease Control and Prevention.

References:

- Bootsma, R. J., & Van Wieringen, P. C. (1992). Spatio-temporal organisation of natural prehension. *Human Movement Science*, 11(1), 205-215.
- Hoff, B., & Arbib, M. A. (1993). Models of trajectory formation and temporal interaction of reach and grasp. *Journal of motor behavior*, 25(3), 175-192.
- Jeannerod, M. (1984). The timing of natural prehension movements. *Journal of motor behavior*, 16(3), 235-254.
- Marteniuk, R. G., Leavitt, J. L., MacKenzie, C. L., & Athenes, S. (1990). Functional relationships between grasp and transport components in a prehension task. *Human Movement Science*, 9(2), 149-176.